# Juralco Edgetec® PosiGlaze™ Balustrade System

# **BPIR Declaration**

Version: 11-23 v1

### **Designated building product: Class 2**

#### **Declaration**

N J & S R Currie Limited trading as HomePlus Hawkes Bay has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

#### **Product/system**

Name	Juralco Edgetec® PosiGlaze™ Balustrade System
Line	
Identifier	

### **Description**

The Juralco Edgetec® PosiGlaze™ Balustrade System is designed for Frameless Glass, from 12mm to 21.52mm, either Base or Side fixed and for Residential or Commercial use. An Interlinking Top Rail (depending on the glass type) may be used. The system is extremely versatile and can be made in a range of configurations to suit most modern architectural requirements and Wind Zones.

#### **Scope of use**

The installation manual details the documents the Juralco Edgetec® PosiGlaze™ Balustrade System refers to in relation to the New Zealand Building Code, the manufacturer's documents, products used in the System, requirements in relation to fixing and surface finishing.

PosiGlaze is the perfect choice for residential to light commercial installations where a frameless glass balustrade is desired. The glass clamping mechanism locks glass panels into position effortlessly. It remains possible to re-align or even remove individual panels after the initial installation has been completed, and it is possible to horizontally align each panel of glass to create an immaculate and seamless finish Where required, an interlinking rail finishes off the system, producing a low-profile modern look.

#### **Conditions of use**

- Only extrusions, components and hardware supplied by or specified by JABP may be used in the Juralco Edgetec® PosiGlaze™ Balustrade System.
- Aluminium extrusions, components, and hardware unless specified are manufactured to 6060 T5 specifications.
- Stainless Steel components, hardware, fixings all components to 304 or 316 grade.
- Glass all glass used in the Juralco Edgetec® PosiGlaze™ Balustrade System
  must conform to the specifications as listed in the Juralco Edgetec® PosiGlaze™
  Balustrade System manual with each panel conforming to AS/NZS 2208 as
  confirmed by the Safety Stamp detailing the manufacturer's description and licence
  number.
- The Juralco Edgetec® PosiGlaze™ Balustrade System must only be installed in accordance with the Juralco Edgetec® PosiGlaze™ Balustrade System Manual.
- Any deviation from that specified in the Juralco Edgetec® PosiGlaze™ Balustrade
   System manual must only be in accordance with the site-specific PS1 with site specific calculations and drawings listing the non-standard details. Contact Juralco
   for more information.
- The Juralco Edgetec® PosiGlaze™ Balustrade System must only be fabricated/installed by a Juralco approved fabricator.

### **Relevant building code clauses**

**B1 Structure** — B1.3.1, B1.3.2, B1.3.3 (c, f, h, j, m), B1.3.4

**B2 Durability** — B2.3.1 (a), B2.3.2 (a, b)

D1 Access Routes — D1.3.3 (j, k)

**F2** Hazardous building materials — F2.3.1, F2.3.3

F4 Safety from falling — F4.3.1

F9 Means of restricting access to residential pools — F9.3.1, F9.3.3

### **Contributions to compliance**

#### NZBC Compliance

- The Juralco Edgetec® PosiGlaze™ Balustrade System has been reviewed by Lautrec Technology Group Ltd to demonstrate compliance with the structural requirements of the New Zealand Building Code and NZS 1170: 2002 occupancy A, B, E, A Other and C3, NZS 3604 up to and including Extras High Wind Zone.
- The Structural Engineering design includes the requirements of B1 Structure, B2 Durability, F2 Hazardous material, and F4 Safety from falling, all from the Building Code.
- Glass used in the Juralco Edgetec® PosiGlaze™ Balustrade System must conform to AS/NZS 2208. Complies with NZS 4223.3.2016
- Separation of dissimilar materials (as relates to B2 compliance) have been reviewed. For other combinations refer to NZS 3604:2011 Section 2.3.3 Separation and Section 4 Durability.

# **Supporting documentation**

The following additional documentation supports the above statements:

BA PosiGlaze Balustrade	11-23 v1	https://www.homeplus.co.nz/assets/Uploads/Eboss/BA-PosiGlaze-Balustrade- 11-23-v1.pdf
Producer Statement Request	11-23 v1	https://ps1.homeplus.co.nz/
HomePlus Warranty	11 December 2023	https://www.homeplus.co.nz/warranty/
Balustrade Care and Maintenance	11 December 2023	https://www.homeplus.co.nz/warranty/c are-and-maintenance/balustrade-care- and-maintenance/

For further information supporting Juralco Edgetec® PosiGlaze™ Balustrade System claims refer to our website.

### **Contact details**

Manufacture location	New Zealand	
Legal and trading name of manufacturer	N J & S R Currie Limited trading as HomePlus Hawkes Bay	
Manufacturer address for service	1014 Omahu Road, Frimley, Hastings 4120	
Manufacturer website	https://www.homeplus.co.nz/find-us/hawkes- bay/	
Manufacturer email	hawkesbay@homeplus.co.nz	
Manufacturer phone number	06 879 8397	
Manufacturer NZBN	9429037343392	

### Responsible person

As the responsible person as set out in Regulation 3, I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore, to the best of my knowledge, correct.

I can also confirm that Juralco Edgetec® PosiGlaze™ Balustrade System is not subject to a warning on ban under <u>s26 of the Building Act</u>.

Signed for and on behalf of N J & S R Currie Limited trading as HomePlus Hawkes Bay:

Nicholas Currie

Nicholas Currie DIRECTOR/OWNER December 2023

N J & S R CURRIE LIMITED TRADING AS HOMEPLUS HAWKES BAY 1014 Omahu Road, Frimley, Hastings 4120 New Zealand 06 879 8397 | https://www.homeplus.co.nz/find-us/hawkes-bay/

# **Appendix**

### **BPIR Ready selections**

Category: Balustrades systems

	Yes	No
Use as pool fencing	×	
Provides an accessible handrail	×	
Use of glass or other brittle material	×	

### **Building code performance clauses**

#### **B1 Structure**

#### B1.3.1

Buildings, building elements and sitework shall have a low probability of rupturing, becoming unstable, losing equilibrium, or collapsing during construction or alteration and throughout their lives.

#### B1.3.2

*Buildings*, *building elements* and *sitework* shall have a low probability of causing loss of amenity through undue deformation, vibratory response, degradation, or other physical characteristics throughout their lives, or during *construction* or *alteration* when the *building* is in use.

#### B1.3.3

Account shall be taken of all physical conditions likely to affect the stability of *buildings*, *building* elements and sitework, including:

- (c) temperature
- (f) earthquake
- (h) wind
- (j) impact
- (m) differential movement

Due allowances shall be made for:

- a. the consequences of failure,
- b. the intended use of the building,
- c. effects of uncertainties resulting from *construction* activities, or the sequence in which *construction* activities occur.
- d. variation in the properties of materials and the characteristics of the site, and
- e. accuracy limitations inherent in the methods used to predict the stability of buildings.

### **B2** Durability

#### B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

 (a) the life of the building, being not less than 50 years, if: those building elements (including floors, walls, and fixings) provide structural stability to the building, or those building elements are difficult to access or replace, or failure of those building elements to comply with the building code would go undetected during both normal use and maintenance of the building

#### B2.3.2

Individual *building elements* which are components of a *building* system and are difficult to access or replace must either:

- (a) all have the same durability
- (b) be installed in a manner that permits the replacement of building elements of lesser durability without removing building elements that have greater durability and are not specifically designed for removal and replacement

#### **D1 Access Routes**

#### D1.3.3

Access routes shall:

- (j) have smooth, reachable, and graspable handrails to provide support and to assist with movement along a stair or barrier
- (k) have handrails of adequate strength and rigidity as required by Clause B1 Structure

### F2 Hazardous building materials

F2.3.1

The quantities of gas, liquid, radiation, or solid particles emitted by materials used in the *construction* of *buildings*, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

F2.3.3

Glass or other brittle materials with which people are likely to come into contact shall:

- a. if broken on impact, break in a way which is unlikely to cause injury, or
- b. resist a reasonably foreseeable impact without breaking, or
- c. be protected from impact.

### F4 Safety from falling

F4.3.1

Where people could fall 1 metre or more from an opening in the external envelope or floor of a *building*, or from a sudden change of level within or associated with a *building*, a barrier shall be provided.

# F9 Means of restricting access to residential pools

F9.3.1

Residential pools must have or be provided with physical barriers that restrict access to the pool or the *immediate pool area* by unsupervised young children (i.e., under 5 years of age).

F9.3.3

A barrier surrounding a *pool* must have no permanent objects or projections on the outside that could assist children in negotiating the barrier. Any gates must

- a. open away from the pool; and
- b. not be able to be readily opened by children; and
- c. automatically return to the closed position after use.